

```
PLEASE ENTER HOST PORT ID:
PLEASE ENTER HOST PORT ID:x
LOGINID:d331sgr
PASSWORD:
TERMINAL (ENTER 1, 2, 3, 4, OR ?):□3
```

```
* * * * *
```

Welcome to MESSENGER (APS Text) at USPTO

The USPTO production files are current through:
May 04 ,1999 for U.S. Patent Text Data.
May 04 ,1999 for U.S. Current Classification Data.
May 04,1999 for U.S. Patent Image Data.

* * * * *

* PLEASE USE 305-9000 FOR NEW TELEPHONE NUMBER *

* * * * *

More U.S. patent data is now available on APS. The new
USOCR file contains patents issued in 1970, plus some
patents that were missing from the USPAT file. See the
Patents News Folder under the Public Folders in e-mail for
more information on using the new file. Thank you.

* * * * *

DISCLAIMER:

Neither the United States Government, nor any agency thereof,
nor any of their contractors, subcontractors or employees make
any warranty, expressed or implied, including any warranty of
marketability of fitness for a particular purpose; nor assumes
any legal liability or responsibility for any party's use, or the
results of such, of the data.

* * * * *

Help Desk --> 703-305-9000

The Help Desk is staffed for APS support 7 days/week.
Monday through Friday: 6:30am - 9:00pm
Saturday, Sunday, Holidays: 8:30am - 5:00 pm

The Help Desk staff at this number will handle all APS related questions.

>>>>>>>>>>>>>>>>>>>>>>>>>>>><<<<<<<<<<<<

NEW SUNDAY HOURS !!!

The APS is available:
 6:30am - 9:00pm Monday through Friday
 7:30am - 5:00pm Saturday, Sunday, Holidays

APS is unavailable Thanksgiving Day, Christmas Day,
and New Year's Day.

```
* * * * *
```

FILE 'USPAT' ENTERED AT 10:21:30 ON 06 MAY 1999

```

* * * * *
*       U. S.   P A T E N T   T E X T   F I L E       *
*
* THE WEEKLY PATENT TEXT AND IMAGE DATA IS CURRENT   *
* THROUGH APRIL 27, 1999.                             *
*
* * * * *

```

=> s infant and posterior and paint

```

      7956 INFANT
      13212 POSTERIOR
      51837 PAINT
L1      2 INFANT AND POSTERIOR AND PAINT

```

=> d 11 1-2 cit

1. 5,658,328, Aug. 19, 1997, Endoscopic assisted mastopexy; Gerald W. Johnson, 623/8; 128/898 [IMAGE AVAILABLE]
2. 4,566,444, Jan. 28, 1986, Portable roentgenographic cephalostat; John L. Spolyar, 606/130; 250/491.1; 378/178, 180 [IMAGE AVAILABLE]

=> s posterior and paint

```

      13212 POSTERIOR
      51837 PAINT
L2      139 POSTERIOR AND PAINT

```

=> s 12 and print

```

      73008 PRINT
L3      17 L2 AND PRINT

```

=> d 13 1-17 cit

1. 5,658,328, Aug. 19, 1997, Endoscopic assisted mastopexy; Gerald W. Johnson, 623/8; 128/898 [IMAGE AVAILABLE]
2. 5,342,513, Aug. 30, 1994, Multipurpose pool skimmer; Edward L. Wall, et al., 210/169; 7/106, 170; 15/1.7; 43/11; 210/238, 471 [IMAGE AVAILABLE]
3. 5,305,233, Apr. 19, 1994, Spectrophotometer for accurately measuring light intensity in a specific wavelength region; Nobukazu Kawagoe, et al., 356/320, 319, 328 [IMAGE AVAILABLE]
4. 5,264,948, Nov. 23, 1993, Image read device; Yoshiya Imoto, 358/474; 355/55; 358/487 [IMAGE AVAILABLE]
5. 5,204,755, Apr. 20, 1993, Radiator system in image recording apparatus; Shinichiro Taga, et al., 358/400; 165/80.3; 355/30; 358/471; 399/130 [IMAGE AVAILABLE]
6. 5,198,909, Mar. 30, 1993, Driving apparatus and method for scanning system for use in image recording apparatus; Masuji Ogiwara, et al., 358/412, 486 [IMAGE AVAILABLE]
7. 5,189,529, Feb. 23, 1993, Reduction/enlargement processing system for an image processing apparatus; Masahiro Ishiwata, et al., 358/451, 428, 448 [IMAGE AVAILABLE]
8. 5,189,528, Feb. 23, 1993, Image reading apparatus; Izumi Takashima,

et al., 358/448, 461, 464 [IMAGE AVAILABLE]

9. 5,175,697, Dec. 29, 1992, Spectrophotometer for accurately measuring light intensity in a specific wavelength region; Nobukazu Kawagoe, et al., 356/320, 407, 419 [IMAGE AVAILABLE]

10. 5,137,623, Aug. 11, 1992, Multi-purpose pool skimmer and method of making same; Edward L. Wall, et al., 210/169; 15/1.7; 210/471, 474, 495 [IMAGE AVAILABLE]

11. 5,120,121, Jun. 9, 1992, Colored lens; David L. Rawlings, et al., 351/162, 160H [IMAGE AVAILABLE]

12. 5,120,120, Jun. 9, 1992, Multifocal optical device with spurious order suppression and method for manufacture of same; Allen L. Cohen, 351/161; 264/1.8; 351/177; 359/565, 571, 574, 575; 623/6 [IMAGE AVAILABLE]

13. 5,116,112, May 26, 1992, Colored lens and method of manufacture; David L. Rawlings, 351/162; 264/1.7; 351/177 [IMAGE AVAILABLE]

14. 5,034,166, Jul. 23, 1991, Method of molding a colored contact lens; David L. Rawlings, et al., 264/1.7, 2.1; 351/162 [IMAGE AVAILABLE]

15. 4,889,421, Dec. 26, 1989, Contact lens with cosmetic pattern; Allen L. Cohen, 351/162 [IMAGE AVAILABLE]

16. 4,136,224, Jan. 23, 1979, Decorative laminated structures and method of making the same; Kazuto Minami, et al., 428/161, 151, 152, 172, 195, 204, 904, 910 [IMAGE AVAILABLE]

17. 3,962,009, Jun. 8, 1976, Decorative laminated structures and method of making same; Kazuto Minami, et al., 156/85; 101/129, 170, 401.1, 467, 488, 491; 156/59, 229, 272.2, 275.1, 275.3, 277; 264/230, 342R; 427/595; 428/15, 151, 910, 913 [IMAGE AVAILABLE]

=> d 13 16 kwic

US PAT NO: 4,136,224 [IMAGE AVAILABLE]

L3: 16 of 17

DETDESC:

DETD(20)

In . . . sensitive pictures of the heat sensitive picture areas are formed on the heat-shrinkable resin sheet and/or the base prior or **posterior** to laminating the heat-shrinkable resin sheet and the base with each other.

DETDESC:

DETD(24)

Each . . . poor absorbability of a heat ray as compared with said heat absorbing material is generally an ink composition or a **paint** composition which comprises a vehicle; a coloring material such as a dye or pigment; and additives such as a plasticizer, . . .

DETDESC:

DETD(25)

Examples of the vehicles to be employed for the ink or **paint** composition included fats and oils such as linseed oil, soybean oil, synthetic drying oils and the like; natural and processed. . .

DETDESC:

DETD(26)

The term "heat sensitive ink composition" is used herein to mean an ink or **paint** composition which is capable of forming a coat film having a high rate of absorption of a heat ray and. . . absorption due to hue, concentration, etc. The term "heat insensitive ink composition" is used herein to mean an ink or **paint** composition forming a coat film having a low rate of absorption of a heat ray. In short, whether the ink. . .

DETDESC:

DETD(81)

Referring . . . a paper (manufactured and sold by Tokushu Paper Making Co. Trade name: S-VELUM. 80g./m.sup.2) was formed with a solid brown-colored **print** layer 72 by gravure-printing. On the **print** layer 72 was gravure-printed a pattern 73 of grains of wood, using a brown ink composition. The face of the. . .

DETDESC:

DETD(117)

Referring . . . of 1.0 mm and a width of 0.5 mm. In printing, the gravure-printing pattern having three steps of depths of **print** pattern, namely 45.mu., 20.mu. and 5.mu. was employed so that there may occur differences in infrared ray absorption rate. As. . . In addition, the concave 146 were colored according to colors of the printed pattern 144. Naturally, the portion having a **print** pattern depth of 45.mu. was caused to form a concave 46 having the greatest depth; and smaller the **print** pattern depth, the depth of concave becomes shallower. But, all the concaves having varied depths coordinate with one another, and. . .

DETDESC:

DETD(128)

Referring . . . formed of repeating rectangles each having a length of 1.0 mm and a width of 0.5 mm. The depth of **print** layer of said printed pattern was 30.mu.. Each of said printed patterns 182, 182' and 182" was colored black, dark. . .

DETDESC:

DETD(138)

On . . . heat-shrinkable resin film was gravure-printed, using a green ink composition containing as a vehicle a polyamide type resin, a gradation **print** coordinating with said colored figures.

DETDESC:

DETD(141)

The . . . was applied with a colored figure printing, was laminated on a thick paper at its side having the colored figure **print**, and was irradiated with a heat ray at an irradiation speed of 5.5 cm./sec., whereby concaves were formed on the. . .

=> d 13 16 kiwc

'KIWC' IS NOT A VALID FORMAT FOR FILE 'USPAT'

ENTER DISPLAY FORMAT (CIT):

ENTER DISPLAY FORMAT (CIT):kwic

US PAT NO: 4,136,224 [IMAGE AVAILABLE]

L3: 16 of 17

DETDESC:

DETD(20)

In . . . sensitive pictures of the heat sensitive picture areas are formed on the heat-shrinkable resin sheet and/or the base prior or **posterior** to laminating the heat-shrinkable resin sheet and the base with each other.

DETDESC:

DETD(24)

Each . . . poor absorbability of a heat ray as compared with said heat absorbing material is generally an ink composition or a **paint** composition which comprises a vehicle; a coloring material such as a dye or pigment; and additives such as a plasticizer, . . .

DETDESC:

DETD(25)

Examples of the vehicles to be employed for the ink or **paint** composition included fats and oils such as linseed oil, soybean oil, synthetic drying oils and the like; natural and processed. . .

DETDESC:

DETD(26)

The term "heat sensitive ink composition" is used herein to mean an ink or **paint** composition which is capable of forming a coat film having a high rate of absorption of a heat ray and. . . absorption due to hue, concentration, etc. The term "heat insensitive ink composition" is used herein to mean an ink or **paint** composition forming a coat film having a low rate of absorption of a heat ray. In short, whether the ink. . .

DETDESC:

DETD(81)

Referring . . . a paper (manufactured and sold by Tokushu Paper Making Co. Trade name: S-VELUM. 80g./m.sup.2) was formed with s solid brown-colored **print** layer 72 by gravure-printing. On the **print** lay 72 was gravure-printed a pattern 73 of grains of wood, using a brown ink composition. The face of the. . .

DETDESC:

DETD(117)

Referring . . . of 1.0 mm and a width of 0.5 mm. In printing, the gravure-printing pattern having three steps of depths of **print** pattern, namely 45.mu., 20.mu. and 5.mu. was employed so that there may occur differences in infrared ray absorption rate. As. . . In addition, the concave 146 were colored according to colors of the printed pattern 144. Naturally, the portion having a **print** pattern depth of 45.mu. was caused to form a concave 46 having the greatest depth; and smaller the **print** pattern depth, the depth of concave becomes

shallower. But, all the concaves having varied depths coordinate with one another, and. . .

DETDESC:

DETD(128)

Referring . . . formed of repeating rectangles each having a length of 1.0 mm and a width of 0.5 mm. The depth of **print** layer of said printed pattern was 30.mu.. Each of said printed patterns 182, 182' and 182" was colored black, dark. . .

DETDESC:

DETD(138)

On . . . heat-shrinkable resin film was gravure-printed, using a green ink composition containing as a vehicle a polyamide type resin, a gradation **print** coordinating with said colored figures.

DETDESC:

DETD(141)

The . . . was applied with a colored figure printing, was laminated on a thick paper at its side having the colored figure **print**, and was irradiated with a heat ray at an irradiation speed of 5.5 cm./sec., whereby concaves were formed on the. . .